

## CLAIMS

1. A light emitting element comprising a plurality of layers interposed between a pair of electrodes opposed to each other,

5            wherein at least one of the plurality of layers is formed of a layer containing a light emitting material, and

             wherein the layer containing the light emitting material is interposed between a layer containing an oxide semiconductor or metal oxide and a material having a higher hole transporting property than an electron transporting property, and a layer containing  
10           an oxide semiconductor or metal oxide and a material having a higher electron transporting property than a hole transporting property.

2. A display device comprises the light emitting element according to claim 1 in a pixel portion.

15

3. A light emitting element comprising a plurality of layers interposed between a pair of electrodes opposed to each other,

             wherein at least one of the plurality of layers is formed of a layer containing a light emitting material, and

20           wherein the layer containing the light emitting material is interposed between a layer containing an oxide semiconductor or metal oxide and a material having a higher hole transporting property than an electron transporting property, and a layer containing an oxide semiconductor or metal oxide, a material having a higher electron transporting property than a hole transporting property and a material which can donate an electron  
25           to the material having a higher electron transporting property than a hole transporting property.

4. A display device comprises the light emitting element according to claim 3 in a pixel portion.

30

5. A light emitting element comprising:  
a pair of electrodes; and  
first to third layers sequentially laminated between the pair of electrodes,  
wherein the first layer contains an oxide semiconductor or metal oxide and a  
5 material having a higher hole transporting property than an electron transporting  
property,  
wherein the second layer contains a light emitting material, and  
wherein the third layer contains an oxide semiconductor or metal oxide and a  
material having a higher electron transporting property than a hole transporting  
10 property.

6. A light emitting element according to claim 5, wherein the first layer  
comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

15 7. A display device comprises the light emitting element according to claim 5  
in a pixel portion.

8. A light emitting element comprising:  
a pair of electrodes; and  
20 first to third layers sequentially laminated between the pair of electrodes,  
wherein the first layer contains an oxide semiconductor or metal oxide and a  
material having a higher hole transporting property than an electron transporting  
property,  
wherein the second layer contains a light emitting material, and  
25 wherein the third layer contains an oxide semiconductor or metal oxide, a  
material having a higher electron transporting property than a hole transporting property,  
and a material which can donate an electron to the material having a higher electron  
transporting property than a hole transporting property.

30 9. A light emitting element according to claim 8, wherein the first layer

comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

10. A display device comprises the light emitting element according to claim 8 in a pixel portion.

5

11. A light emitting element comprising:

a pair of electrodes; and

first to fourth layers sequentially laminated between the pair of electrodes,

wherein the first layer contains an oxide semiconductor or metal oxide and a  
10 material having a higher hole transporting property than an electron transporting property,

wherein the second layer contains a light emitting material,

wherein the third layer contains an oxide semiconductor or metal oxide and a  
material having a higher electron transporting property than a hole transporting property,  
15 and

wherein the fourth layer contains an oxide semiconductor or metal oxide, a  
material having a higher electron transporting property than a hole transporting property,  
and a material which can donate an electron to the material having a higher electron  
transporting property than a hole transporting property.

20

12. A light emitting element according to claim 11, wherein the first layer  
comprises molybdenum oxide and 4,4(-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

13. A display device comprises the light emitting element according to claim 11  
25 in a pixel portion.

14. A light emitting element comprising:

a pair of electrodes; and

first to fourth layers sequentially laminated between the pair of electrodes,

wherein the first layer contains an oxide semiconductor or metal oxide and a  
30

material having a higher hole transporting property than an electron transporting property,

wherein the second layer contains a light emitting material,

5 wherein the third layer contains an oxide semiconductor or metal oxide and a material having a higher electron transporting property than a hole transporting property, and

wherein the fourth layer contains a material having a higher electron transporting property than a hole transporting property and a material which can donate an electron to the material having a higher electron transporting property than a hole transporting property.

10

15 15. A light emitting element according to claim 14, wherein the first layer comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

16. A display device comprises the light emitting element according to claim 14 in a pixel portion.

17. A light emitting element comprising:

a pair of electrodes; and

20 first to fourth layers sequentially laminated between the pair of electrodes,

wherein the first layer contains an oxide semiconductor or metal oxide and a material having a higher hole transporting property than an electron transporting property,

wherein the second layer contains a light emitting material,

25 wherein the third layer contains an oxide semiconductor or metal oxide and a material having a higher electron transporting property than a hole transporting property, and

wherein the fourth layer contains an oxide semiconductor or metal oxide and a material having a higher hole transporting property than an electron transporting property.

30

18. A light emitting element according to Claim 17, wherein the first layer and the fourth layer are formed using the same material.

5           19. A light emitting element according to claim 17, wherein the first layer comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

20. A display device comprises the light emitting element according to claim 17 in a pixel portion.

10

21. A light emitting element comprising:

a pair of electrodes; and

first to fourth layers sequentially laminated between the pair of electrodes,

15           wherein the first layer contains an oxide semiconductor or metal oxide and a material having a higher hole transporting property than an electron transporting property,

wherein the second layer contains a light emitting material,

20           wherein the third layer contains an oxide semiconductor or metal oxide, a material having a higher electron transporting property than a hole transporting property, and a material which can donate an electron to the material having a higher electron transporting property than a hole transporting property, and

25           wherein the fourth layer contains an oxide semiconductor or metal oxide, a material having a higher electron transporting property than a hole transporting property.

22. A light emitting element according to Claim 21, wherein the first layer and the fourth layer are formed using the same material.

30           23. A light emitting element according to claim 21, wherein the first layer comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

24. A display device comprises the light emitting element according to claim 21 in a pixel portion.

5           25. A light emitting element comprising:

a pair of electrodes; and

first to fifth layers sequentially laminated between the pair of electrodes,

wherein the first layer contains an oxide semiconductor or metal oxide and a material having a higher hole transporting property than an electron transporting property,

wherein the second layer contains a light emitting material,

wherein the third layer contains an oxide semiconductor or metal oxide and a material having a higher electron transporting property than a hole transporting property,

15           wherein the fourth layer contains an oxide semiconductor or metal oxide, a material having a higher electron transporting property than a hole transporting property, and a material which can donate an electron to the material having a higher electron transporting property than a hole transporting property, and

wherein the fifth layer contains an oxide semiconductor or metal oxide and a material having a higher hole transporting property than an electron transporting property.

26. A light emitting element according to Claim 25, wherein the first layer and the fifth layer are formed using the same material.

25

27. A light emitting element according to claim 25, wherein the first layer comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

28. A display device comprises the light emitting element according to claim 25 in a pixel portion.

30

29. A light emitting element comprising:

a pair of electrodes; and

first to fifth layers sequentially laminated between the pair of electrodes,

5 wherein the first layer contains an oxide semiconductor or metal oxide and a material having a higher hole transporting property than an electron transporting property,

wherein the second layer contains a light emitting material,

10 wherein the third layer contains an oxide semiconductor or metal oxide and a material having a higher electron transporting property than a hole transporting property,

15 wherein the fourth layer contains a material having a higher electron transporting property than a hole transporting property and a material which can donate an electron to the material having a higher electron transporting property than a hole transporting property, and

wherein the fifth layer contains an oxide semiconductor or metal oxide and a material having a higher hole transporting property than an electron transporting property.

20 30. A light emitting element according to Claim 29, wherein the first layer and the fifth layer are formed using the same material.

31. A light emitting element according to claim 29, wherein the first layer comprises molybdenum oxide and 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl.

25

32. A display device comprises the light emitting element according to claim 29 in a pixel portion.